

FLEX-Elektrowerkzeuge GmbH
 Bahnhofstraße 15
 71711 Steinheim
 Phone +49 7144 828-0
 Fax +49 7144 25899
 info@flex-tools.com
 www.flex-tools.com



FLEX
 Das Original

Burnishing machine TRINOXFLEX Set

BSE 14-3 100 Set

Order number 433.438



Technical attributes	
Power input	1400 watt
Power output	880 watt
Max. tool Ø	125 mm
Tool width	100 mm
Tool fixture	19 mm
No load speed	1000-3500 rpm
Cable length	4,0 m
Weight	2,9 kg

Standard equipment	
1 sanding attachment for burnishing BS 100	433.462
1 rubber air roller	433.896
1 air pump	256.284
1 fleece A 280/fine	256.975
1 sanding-polishing sleeve, S 600	436.429
1 sanding-polishing sleeve, S 1500	436.437
1 MESHFLEX sanding sleeve A 400	434.612
3 ZIRCOFLEX sanding sleeves P 80	3 pieces of 434.515
3 ZIRCOFLEX sanding sleeves P 120	3 pieces of 434.523
3 CERAFLEX sanding sleeves K 120	3 pieces of 434.566
3 CORUFLEX sanding sleeves P 180	3 pieces of 434.574
1 carrying case L-BOXX® 238	414.093
1 case insert	433.918

Burnishing machine TRINOXFLEX Set

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing and pipe belt sanding
- + Variably adjustable burnishing attachment, allows working close up to the edge, also suitable for narrow rollers, incl. edge guide
- + Tool-free grinding tool change via a patented quick-change system
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Adjustable guard: for sanding tools up to Ø 125 mm
- + Spindle lock
- + For optimum finishing of various materials, for burnishing, texturing, polishing, brushing, smoothing, de-rusting and deburring steel and stainless steel surfaces



Lyngbygårdsvej 28a
8220 Brabrand
Danmark
Tlf. 0045-86263533
e-mail AB@absvejs.dk
www.abshop.dk